

Challenger

MODEL	MT225	MT255	MT265	MT275	MT285	MT295
GROSS ENGINE HP (KW)	23.3 (17.4)	28.4 (21.2)	33 (24.6)	40.1 (30)	40.1 (30)	44.2 (33)
PTO HP (KW)	19.0 (14.2)	24.2 (18)	27 (20.1)	32.4 (24.2)	32.4 (24.2)	37.0 (27.6)
TRANSMISSION Standard	Hydrostatic	Constant Mesh	PowerShuttle	Manual Shuttle	PowerShuttle	PowerShuttle
# of Gears	NA	9F/3R	16F/16R	8F/8R	16F/16R	16F/16R
# of Ranges	2	3	4	2	4	4
Creeper	NA	NA	Standard	NA	Standard	Standard
PTO						
Type	Independent	Live	Independent	Independent	Independent	Independent
Output Locations						
Rear	Standard	Standard	Standard	Standard	Standard	Standard
Mid	Standard	Optional	Optional	Optional	Optional	N/A
3-POINT HITCH	1.210 (5.40)	1.004.(000)	2.755 (1.250)	2.755 (1.250)	2.755 (1.250)	2.006 (1.400)
Lift Capacity @ Hitch Point	1,210 (549)	1,984 (900)	2,755 (1,250)	2,755 (1,250)	2,755 (1,250)	3,086 (1,400)
Lift Capacity @ 24": lbs (kg) HYDRAULICS	694 (315)	1,323 (600)	2,100 (950)	2,100 (950)	2,100 (950)	2,600 (1,180)
Total Pump Flow: gpm (lpm)	7.9 (30)	9.9 (37.6)	12.2 (46.2)	12.2 (46.2)	12.2 (46.2)	12.6 (47.8)
FOUR WHEEL DRIVE FRONT AXLE	Standard	Standard	Standard	Standard	Standard	Standard
WEIGHT Lbs (kg)	1,672 (758)	2,248 (1,020)	3,041 (1,380)	3,107 (1,410)	3,174 (1,440)	4,277 (1,941)
All Ag Tires					,	

MODEL	MT265 HYDRO	MT285 HYDRO	MT295 HYDRO	
GROSS ENGINE HP (KW)	33.0 (24.6)	40.1 (30)	44.2 (33)	
PTO HP (KW) TRANSMISSION	25.0 (18.7)	31.7 (23.6)	36.0 (26.9)	
Standard	Hydrostatic	Hydrostatic	Hydrostatic	
# of Ranges	3	3	2-mechanical 2-powershift	
PTO			·	
Type	Independent	Independent	Independent	
Output Locations				
Rear	Standard Standard	Standard		
Mid	Optional	Optional	Optional	
3-POINT HITCH				
Lift Capacity @ Hitch Point	2,866 (1,300)	2,866 (1,300)	3,086 (1,400)	
Lift Capacity @ 24": lbs (kg)	1,940 (880)	1,940 (880)	2,600 (1,180)	
HYDRAULICS				
Total Pump Flow: gpm (lpm)	9.6 (36.2) 9.6 (36.2)	12.6 (47.8)		
FOUR WHEEL DRIVE FRONT AXLE	Standard Standard	Standard		
DRY WEIGHT LBS (KG)	2,981 (1,353)	3,114 (1,413)	4,331 (1,965)	

- •The Challenger MT200 Series compact tractors feature up to 20% more operator area than the major competitive compact tractors.
- •200 Series tractors are built for operator safety with seat belts and Rollover Protective Structure (ROPS) as standard equipment. Certain models offer folding ROPS to allow for extra-low clearance when you need it.
- •All MT200 Series tractors feature rugged steel hoods and fenders for added durability.
- •Available with your choice of R4 industrial, R3 turf, or R1 ag tires.
- •Available with LSW radial for golf course MT265 MT285.
- •More than 25 key features preferred by compact tractor users including 4WD, power steering, and choice of standard, shuttle and hydrostatic transmissions.
- •Rugged, cast-iron construction.
- •A full range of implements and attachments are available to meet all your working requirements.